



SECTION B-B
Scale: $\frac{3}{8}'' = 1'-0''$



SECTION A-A
Scale: None



SECTION C-C
Scale: Full

*In order to insure a smooth and acceptable surface, 420.03.11 (Construction Joints) will be strictly adhered to.

- Notes:
- Place vertical paraffin joint, shown hatched, at centerline of pier on multi span bridges.
 - Joints shall be formed by placing alternate sections.
 - The placement of adjacent sections shall have a 40 hour delay between placements.
 - Railing and fencing not shown.

FHWA APPROVAL
DATE:

APPROVAL	
<i>L. S. Friedman</i> DIRECTOR OFFICE OF BRIDGE DEVELOPMENT DATE: 12/1/93	
REVISIONS	
SHA	FHWA
12-1-93	
6-1-05	

STATE OF MARYLAND
 DEPARTMENT OF TRANSPORTATION
 STATE HIGHWAY ADMINISTRATION
 OFFICE OF BRIDGE DEVELOPMENT

PARAPET CONTROL JOINT AND SINGLE CONDUIT
 PLACEMENT WITH 34" F-SHAPE PARAPET AND
 PARAPET WITH SIDEWALK

STANDARD NO. BR-SS(6.09)-05-70A

SHEET 4 OF 4

SUPER-CONCRETE WORK